SPECIFICATIONS

Model	• HM 1800B		
Print Head	Water-based Kyocera print head		
Pint head Qty	• 4—8 pcs		
Max Printing Resolution	• 600 x 1800 dpi		
Production Speed	 600 x 600 dpi (2pass) 260m²/hr 	 600 x 900 dpi (3pass) 190m²/hr 	 600 x 1200 dpi (4pass) 130m²/hr
Printing Height	• 2—30 mm		
Media Conveying	• Continuous belt-conveying, Auto constant tension feeding&taking up, Fabric spreading, Tension-free entry unit(optional		
Max Printing Width	• 1900 mm		
Max Media Width	• 1920 mm		
Dimension (L/W/H)	 Printer: 4656 mm x 2304 mm x 2277 mm Dryer: 2190 mm x 2850 mm x 1780 mm Package: 4850 mm x 2250 mm x 2250 mm Package: 2280 mm x 2960 mm x 1730 mm 		
Ink Type	• Reactive, acid, sublimation (direct or transfer), pigment		
Ink Color	• Cyan, Magenta, Yellow, Black+four spot colors (optional)		
Ink Supply	Peristaltic-pump ink supply, Ink degassing, Auto negative pressure system		
Belt Cleaning	Auto brush and sponge roller washing system		
Media Type	• Cotton, linen, silk, nylon, polyester, blended, elastic fabrics, etc		
Max Roll Diameter	• 400 mm (standard unwinder&winder roll)		
Max Roll Weight	• 100 kg (Full width, standard unwinder&winder roll)		
Drying	• Belt + Hot air + IR		
Rip Software	Neostampa or Texprint		
Power supply	 Printer: AC380V three phase 30A (6.5kW)+27A (6kW) 50Hz/60Hz Dryer: AC380V three phase 22A (15.9kW) 50Hz/60Hz 		
Compressed water supply	• 0.6 Mpa 0.9m³/hr		
Compressed air supply	• 0.6 Mpa 0.15m³/hr (dry,no oil or water)		
Working Environment	 Temperature: 20~28°C (68~77 F) Relative humidity: 45-60% (no condensing) 		



Shenzhen HOMER Textile Tech Co.,Ltd Add:The Third Factory, NO.322 Yuanhu Road, Longgang District, Shenzhen, China. Tel: +86 0755-23061585 Fax: +86 0755-23217841 E-mail: info-homer@hanglorygroup.com Http://www.homertech.com



HM 1800B

Industrial high-speed conveying-belt direct-to-textile digital printer

- Outstanding printing speed and quality; excellent reliability and stability.
- Advanced mechanic and software design; High-efficiency data processing technology.
- Support diversified printing applications; Widely used in reactive, acid and disperse direct printing.
- Top-level R&D team ensures continuous innovation and product optimization, and keeps us at the technology forefront in digital inkjet printing.
- Strong worldwide service team responds promptly to your questions and concerns.
- Cost-effective products bring you more business and profit.


© The above information is for reference only. Shenzhen Homer Textile Tech Co., Ltd. reserves the right of final interpretation. Descriptions, illustrations and specifications hereof are subject to change without prior notice. Final details shall be subject to contract signed.





HM 1800B

Workflow



Creative dual-row printhead allignment

Backed by the creative printhead set-up, the precision of inkdrop has been greatly enhanced to ensure printing quality.

Up to 260 m²/hr printing speed

Attributed to advanced mechanical structure and self-developed high-performance hardware & software system, the equipment delivers printing speed up to 260 m²/hr.


Tension-adjustable continuous winding/unwinding control technology

Equipped with full servo motors for feeding and taking-up, the stepping accuracy of the machine is greatly enhanced. The laser sensor at the winding section measures the roll diameter in real time for constant and smooth winding.

Industrial ink supply system: Peristaltic-pump ink supply+Automated negative pressure monitoring &adjusting system+Efficient ink degassing

Peristaltic pumps keep the kinetic energy of ink supply at a constant level; negative pressure is detected and adjusted in real time automatically; the efficient degassing modules clear the bubbles in ink tubes to avoid ink starvation. These three designs work together to make ink spurted out smoothly to provide higher printing stability for industrial continuous production.





Magnetic linear motor and steel rail beam

The rail beam is made of high-strength steel with top straightness. Combined with magnetic levitation motor, it imporves the stability and smoothness of the printhead carriage's back and forth movement.







Reactive printing

Acid printing

Disperse printing



The brand new visible operation interface includes automatic order management and automatic cost calculation etc.. One operator is now able to control multiple machines with the smart interface. It is easy to learn and use, greatly improves work efficiency.

Intertek Intertek Certification



High speed belt cleaning system saves energy and cleans the belt more thoroughly. A tidy belt keeps the textile free from dirt.



Kyocera-certified original ink

pure color and smooth output.

The Homer ink with Intertek certification


has been certified by Kyocera, matching

well with Kyocera print heads. It delivers

Intelligent constant-moisturizing capping system and Creative auto-wiping printhead self-cleaning system

Built-in humidifier enables mist spray automatically, so constant moisturizing of nozzles guarantees the stability of ink supply system and prevents blocked nozzles caused by dry ink. Automated head wiping removes the residual ink on the nozzle surface, to guarantee continuous printing.

The specialized conveyor belt has a smaller tension force. Together with a large-diameter roll it improves the accuracy and stability of conveying process.



Anti-scratch printhead protection design

The Anti-scratch system with laser sensors will suspend the printhead carriage for any potential media irregularities, to prevent damage to the printheads and maximize printheads' working life.

Specialized conveyor belt for digital printing

Automated textile rolling design

This flexible rolling system avoids the indentation of sensitive fabric and improve the output quality.

Intelligent and user-friendly operation interface

Industrial-level stable performance

This equipment has passed the 7x24 hour reliability test. The high-end industrial design and sound digital solutions have made it a perfect choice for industrial production.

Efficient belt cleanning system