


HT3020UV

UV Flatbed Inkjet Printer

- Kyocera Series



*Illustration purpose

Optional Models:

- **HT1610UV** Small format, lightweight, economical
- **HT2512UV** Classic for a decade, showcasing stable quality (Multiple Available)
- **HT3020UV** Ultra-large format width-to-length ratio
- **HT3116UV** Large format high-speed flatbed solution

Range of Large Format Printers with high speed drop on demand piezo inkjet technology.
Outstanding Performance:



Automatic Negative
Pressure System



Automatic Height
Measurement System



Adjustable UV
Curing Power



Sensitive Collision Avoidance
Device for the Carriage



Adjustable Suction Area



Optional Anti-Static Bar



Integrated Software Functions
(Require ADP / Computer)




High-Quality Imported
Components

UV Flatbed Inkjet Printer - Kyocera Series

Model		HT1610UV		HT2512UV			HT3020UV		HT3116UV	
Printing Information										
Printhead		Kyocera								
Number of Printhead		2-4 Pcs (1-Row)	2-4 Pcs (1-Row)	4-8 Pcs (2-Row)	8-10 Pcs (Symmetrical Row)	2-12 Pcs (3-Row)	4-8 Pcs (2-Row)	8-10 Pcs (Symmetrical Row)	4-8 Pcs (2-Row)	8-10 Pcs (Symmetrical Row)
Resolution		1200*1200 DPI				605*1800 DPI	1200*1200 DPI			
Production Mode	Draft	36 m ² /h	62 m ² /h	96 m ² /h	100 m ² /h	113 m ² /h	90 m ² /h	125 m ² /h	90 m ² /h	120 m ² /h
	Production	27 m ² /h	44 m ² /h	70 m ² /h	76 m ² /h	93 m ² /h	66 m ² /h	95 m ² /h	66 m ² /h	90 m ² /h
	Quality	20 m ² /h	31 m ² /h	52 m ² /h	55 m ² /h	68 m ² /h	48 m ² /h	73 m ² /h	51 m ² /h	64 m ² /h
Print Mode		Unidirectional & Bidirectional								
Media Ink										
Max. Print Width		1.6*1.0 m	2.5*1.2 m				3.0*2.0 m		3.1*1.6 m	
Max. Media Thickness		100 mm								
Media Type		Signage, acrylic, metal sheets, PVC sheets, KT boards, corrugated boards, plastics, PC, ABS, 3C, and more.								
Ink		Environmentally friendly UV / LED curable ink (VOC free)								
Ink Color		CMYK、Lc、Lm、W (Varnish optional)	CMYK、Lc、Lm、W、V							
Features										
UV Curing		LED								
Interface		USB								
RIP Support		Caldera / Onyx (Optional Purchase)								
Image Format		PDF, JPEG, TIFF, EPS, AI,etc.								
Dimension Weight										
Printer Size(L*W*H)		3.44*2.21*1.28 m	4.67*2.51*1.38 m				5.22*2.71*1.38 m		5.22*3.24*1.38 m	
Printer Net Weight		570 KG	1150 KG				1520 KG		1540 KG	
Printer Gross Weight		990 KG	1745 KG				2330 KG		2160 KG	
Power Supply Environment										
Power Consumption		5.3 kW (27A)	8.3 kW (20A)							
Power Supply		230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE							
Environment		Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)								
Others		Requires ADP / Computer								

Industrial Digital Inkjet Printing Solution Provider

Independent printhead-drive technology 	Self-developed control system 	Self-developed MES system 	Independent ink industrial chain 	Remote service maintenance system and local services 
--	---	---	--	--



Shenzhen HandTop Tech Co.,Ltd

Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)

Tel: +86 0755-23080896 / 23062862

Fax: +86 0755-23217841

E-mail: info@hanglorygroup.com

Web: www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation.
Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V3.0/2025