

Characteristics of Kyocera Series	Characteristics of Ricoh Series
<p>✔ Overall reduction in printhead usage</p> <p>Kyocera single printhead can achieve a printing width of 108 - 112 mm. Achieve high-quality printing with fewer Printheads, reducing the difficulty and time of printhead stitching.</p>	<p>✔ High Productivity: More efficiency, faster delivery, shorter cycles</p> <p>Max. droplet ignition frequency of 50KHz, an 80% increase in ink discharge per unit time, meeting high-speed production needs. Save twice the printing time under the same resolution printing mode.</p>
<p>✔ Compatible with high productivity and high quality</p> <p>High productivity can be achieved even in high-resolution image printing.</p>	<p>✔ High Resolution: Realistic images, textures, details</p> <p>Minimum droplet size reduced from 7pl to 5pl, achieving higher jetting accuracy. Achieve smoother, more delicate printing effects without generating a grainy texture.</p>
<p>✔ Implementation of multi-level grayscale printing</p> <p>Small droplets are suitable for high Resolution images. Large droplets make colors more vibrant. Combination of multi-level droplets results in a subtle and natural color gradient.</p>	<p>✔ Enhanced ink compatibility, extending the lifespan</p> <p>Each print Printhead has enhanced bonding technology to improve durability. Further enhances compatibility between the Printhead and UV ink.</p>
<p>✔ Suitable for high reliability in demanding industrial environments</p> <p>Stainless steel printhead panel and metal shell. Widely used in various fields with numerous successful cases and proven performance.</p>	

Outstanding Performance of HandTop UV Flatbed Inkjet Printer	
<p>✔ Automatic Negative Pressure System</p> <p>Automatically controls negative pressure, achieving precise software visualization and setting of negative pressure parameters.</p>	<p>✔ Adjustable UV Curing Power</p> <p>LED light power can be adjusted for better curing effects.</p>
<p>✔ Automatic Height Measurement System</p> <p>Can measure heights of up to 100mm for media, automatically detecting printing height.</p>	<p>✔ Sensitive Collision Avoidance Device for the Carriage</p> <p>The carriage is equipped with a collision avoidance emergency stop device to prevent accidental scraping that may damage the printhead.</p>
<p>✔ Adjustable Suction Area</p> <p>The suction area can be adjusted according to actual conditions, supporting both suction and blowing adjustments to simplify media loading and unloading.</p>	<p>✔ Optional Anti-Static Bar</p> <p>The anti-static bar kit can remove static electricity from the media surface, significantly reducing ink mist and improving printing quality.</p>
<p>✔ Integrated Software Functions (Require ADP / Computer)</p> <p>Allows users to adjust all functions within the software, enabling RIP and printing simultaneously to enhance work efficiency.</p>	<p>✔ High-Quality Original Imported Components</p> <p>Components are sourced from top global suppliers in Japan, Germany, Italy, etc.</p>