

Technical Parameters:

Model	HT2540UV					
Printing Information						
Printhead	GEN6					
Number of Printheads	4-16 pcs (4-Row)					
Pass	4 Pass	6 Pass	8 Pass	9 Pass	12 Pass	16 Pass
Productivity(2.5*4.0m full width)	141 m ² /h	95.5 m ² /h	71 m ² /h	63 m ² /h	46.7 m ² /h	35.3 m ² /h
Printing Modes	Bidirectional high speed					
Media & Ink						
Max. Print Width	2.5*4.0 m (W*L)					
Max. Media Thickness	100 mm					
Media	Background wall decoration, steel plates, soundproof cotton, waterproof fabrics, water entertainment equipment, and other large-format media.					
Ink Type	Environmentally friendly UV-curable ink (VOC-free)					
Ink Color	CMYK + White + Spot colors (up to 10 colors supported)					
Features						
Curing	LED Curing (adjustable power)					
Transfer	USB					
RIP Support	Caldera / Onyx (Optional Purchase)					
Input	PDF, JPEG, TIFF, EPS, AI,.....					
Dimensions & Weight						
Printer Dimensions	5420*5026*1580 mm (L*W*H)					
Net Weight	3000 KG					
Power & Environment						
Power Consumption	12.5kW (57A)					
Power Supply	220V					
Environmental Requirements	Independent, clean, low-dust, low-light workspace with good ventilation					
	Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)					
	Relative Humidity: 30% ~ 70% (non-condensing)					
Others	Requires ADP / Computer					

Industrial Digital Inkjet Comprehensive Solution Provider



Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Industrial-grade PLC control module



Independent ink industrial chain



Remote service maintenance system and local services

Shenzhen HandTop Tech Co., Ltd.

www.hanglorygroup.com

Add: Baolong 3rd Road and Gaoke Avenue Intersection, Longgang District, Shenzhen, Guangdong

Tel: (+86)0755-2308 0896

Fax: (+86)0755-2321 7841

E-mail: info@hanglorygroup.com

©Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.



V1.0/2025