





# Elite2504


**HIGH-SPEED SINGLE PASS CORRUGATED DIGITAL PRINTER**  
**The Star of Efficiency in Single Pass**








 <b>VERSATILE</b>	 <b>FAST</b>	 <b>STABLE</b>	 <b>ECONOMICAL</b>
<p><b>Broad Range of Applications</b> Meeting the needs of large/medium/small batch, multi-version, customization, personalization, and variable data orders.</p> <p><b>Increased Expandability</b> Supporting multiple process modules and connect seamlessly</p>	<p><b>High Production Speed</b> 100m/min</p> <p><b>One Step Operation in the Same Media Specification</b></p> <p><b>High Efficiency, Fast Delivery, Short Turnover</b></p>	<p><b>24/7 Industrial-grade Stability</b></p> <p><b>Seamless Job Change in Production for Complex Full-page Printing</b></p>	<p><b>Smaller Footprint</b></p> <p><b>Lower Ink Consumption</b></p> <p><b>Overall Cost Savings</b></p>

**Provide end-to-end high-quality total solutions including equipment, software, ink, consumables and after-sales support.**

## Specifications

Model	Elite 2504			
Printhead	Industrial-grade piezoelectric ceramic printhead			
Ink Type	Water-based pigment/dye ink			
Drying System	Air dry			
Inking System	Negative pressure fully automatic ink supply system			
RIP Software	Third-party professional RIP software			
Operating Software	Elite2504 printing control software			
Printhead Configuration	 1 - 4 colors (CMYK), with up to 10 printheads per color			
Max. Speed	100 m/min	75 m/min	50 m/min	...
DPI Resolution (Feeding direction * Width direction)	400 * 600	600 * 600	900 * 600	...
Printing Media Information	Suitable media width: 400 - 2500 mm			
	Minimum media length: 400 mm			
	Maximum media board size: 2500 * 4000 mm (can be extended when not limited by stacking, etc.)			
	Material thickness: 1.5 - 15 mm			
	Media types: Yellow cardboard, White cardboard			
Max. Printing Width	1080 mm			
Feeding Mode	Front edge			
Feeding Accuracy (In feeding direction)	±1 mm			
Printing Registration Accuracy	±0.2 mm			
Air Pressure Requirement	Pressure: 0.6 - 0.84 Mpa, Flow rate ≥ 150 L/min, filtered air			
Environment Requirement	Relative humidity: 45 - 65%, Ambient temperature: 22 - 28 °C			
Power Consumption	AC380 - 400 V 3P+PE, 150 A, 50/60 Hz, Total power: 34 kW			

## Industrial Digital Printing Solution Provider

<b>Independent printhead-drive technology</b> 	<b>Self-developed control system</b> 	<b>Self-developed MES system</b> 	<b>Independent ink industrial chain</b> 	<b>Remote service maintenance system and local services</b> 
--	---	---	--	--



### Shenzhen Hanway Industrial Digital Equipment Co.,Ltd.

Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen  
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)

Tel: +86 0755-23080896  
Fax: +86 0755-23217841

Web: [www.hanglorygroup.com](http://www.hanglorygroup.com)  
E-mail: [info@hanglorygroup.com](mailto:info@hanglorygroup.com)

©The above information is for reference only, Shenzhen Hanway Industrial Digital Equipment Co.,Ltd. reserves the right of final interpretation and is subject to change without notice, final information is subject to contract.